



Manufactured from Red Balau, Arcadia has low variability in appearance. The material is sourced with sustainable methods from Indonesia and is less dense than its other tropical counterparts, but it does not compromise on durability. This product is utilized in exterior applications primarily for decking, but can be moulded to cladding profiles as well.

TECH SPECS

Janka Hardness: 1600 lbs

Fire Rating: Class A Durabilty: Class 2

Movement:

Radial Shrinkage: 5.5% Tangential Shrinkage: 10.1%

Grade: FAS

Finish:

Oil-Based Wood Stabilizer

 Finished on 1 show face and sealed on back and sides unless otherwise noted

VOC Range: 215 g/L

Width: 4 - 6"

Thickness: 3/4 - 1" Length: up to 18' Variability Score: 2

For use in **exterior** applications

INSTALLATION

Alpha Decking is compatible with the following installation methods:

- Clip Systems
- Hidden Fasteners
- Visible Fasteners

A proper acclimation period is required once material is received to ensure best results.

Decking should be installed on joists 16 inches on center, as per code.

CARE & MAINTENANCE

Plan to inspect decking and cladding annually to determine if reapplication is needed. In shaded areas or ceiling/soffit applications, reapplication may not be as frequent. Please refer to our full care & maintenance instructions for more information.

CERTIFICATIONS & LEED ELIGIBILITY

- FSC certified material
- LEED Eligibility:
 - 2 Points: MR7 Materials & Resources | Sourcing of Raw Materials
- Other points available for site-specific attributes



The mark of responsible forestry



BIM Objects are available on our website for all Alpha products. Please visit http://www.mcilvain.com/bim-library to download.